


## PRODUCT IMAGE

## TECHNICAL DRAWING





		$\sim$			$\sim$	 \ F	$T \wedge I$	
$\mathbf{P}$	R	( )	1 )	ш	(	 ) ⊢	ΙДΙ	ILS
	ı 🔪	$\cup$	$\boldsymbol{L}$	$\cup$	$\cup$			

Description	Angle Valve with Wall Flange				
Product Code	COS-CHR-103053				
Connection Size (mm)	N.A				
Aerator Size	N.A				
Flow Rate	32.24 LPM @ 3 bar				
Flow Regulator	N.A				
Recommended Water Pressure	0.5 Bar - 5 Bar				
Material Composition Specification in Percentage	Brass Ingots as per IS:1264-1997- Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)  Brass Rod as per IS:319-1989- Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)  Brass Sheets as per IS:410-1977- Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)				
Cartridge Specification	Fittings: Components have WRAS Approved for food grade conformity with Brass Housing and Spindle Life Cycle EN 200: 200,000 cycles (Standard), - 4.0 LAC Cycles as per EN 200*				
Water Tightness	12 bar (Pass)				
Pressure Resistance	20 bar (pass)				
Finish	<b>Plating:</b> Nickel-8.0 micron Chromium-0.20 micron, Salt Spray (300 hrs + Validated), Adhesion (Pass)				
Available Colour Finishing	Chrome (CHR)				

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries.110% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.