	esscobathware.com
PRODUCT IMAC	GE TECHNICAL DRAWING
	Operating Lever Wall Flange
PRODUCT DETAILS	Expected Dart Kit of Single Lewer In well Diverter
Description	Exposed Part Kit of Single Lever In-wall Diverter (Suitable for Item ALE-055)
Product Code	COS-CHR-103055NK
Connection Size (mm)	N.A
Aerator Size	N.A
Flow Rate	N.A
Flow Regulator	N.A
Recommended Water Pressure	0.5 Bar - 5 Bar
Material Composition Specification in Percentage	Brass Rod as per IS:319-1989- Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) Brass Sheets as per IS:410-1977- Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder) ABS - Specific Gravity (g/cm2) - (1.06-1.10), Melt Mass Flow Rate (g/10 min.) - (20-26), Rockwell Hardness - (95-115), DTUL @ 66 psi (0.45 MPa) (0C) - (78-102) NBR 70 - Rubber Parts
Cartridge Specification	N.A
Water Tightness	N.A
Pressure Resistance	N.A
Finish	Plating: Nickel-8.0 micron Chromium-0.20 micron, Salt Spray (300 hrs + Validated), Adhesion (Pass)
Available Colour Finishing	Chrome (CHR)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries.t10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.