ESSLU Maguar	esscobathware.com
PRODUCT IMAG	GE TECHNICAL DRAWING
PRODUCT DETAILS Description	Hand Shower Pack (Multifunction 80mm dia Round Shape Hand Shower
Product Code	with 1.5M long spirochrome flex hose & wall bracket, 1931, 547D8 & 555) SAE-CHR-1931SH555
Connection Size (mm)	N.A
Aerator Size	N.A
Flow Rate	Normal - 14.78 LPM @ 3 bar Massage - 7.59 LPM @ 3 bar
Flow Regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure one can regulate the flow rate
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Material Composition Specification in Percentage	 Brass Rod as per IS:319-1989- Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) SS Sheet as per AISI 304- Ni (8.000-11.000), Cr (18.000-20.000), Mn (0.0-2.000), C (0.0-0.080), Iron (Remainder) ABS Specification- Specific Gravity g/cm2 (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)
Technology	Advanced Rubit - Lime scale deposits sticking to the shower face can be eas rubbed off by hand or flannel
Mount Type	N.A
Spray Modes	Normal and Massage functions
Finish	Salt Spray (200 hrs+Validated), Adhesion (Pass)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries.t10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.