



|   |   |
|---|---|
| <b>Product Code</b>                                     | STE-CHR-107081  |
| <b>Description</b>                                      | In-wall Flush Valve with Wall Flange, Size 25 mm (With Exposed and In-wall parts)   |
| <b>Flow Rate</b>  | 47.00 LPM @ 3 bar   |
| <b>Recommended Water Pressure</b>                       | 0.5 Bar - 5 Bar   |
| <b>Material Composition Specification in Percentage</b> | <p><b>Brass Ingots as per IS:1264-1997</b><br/>Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p><b>Brass Rod as per IS:319-1989</b><br/>Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>ABS</b> - Specific Gravity (g/cm<sup>2</sup>) - (1.06-1.10), Melt Mass Flow Rate (g/10 min.) - (20-26), Rockwell Hardness - (95-115), DTUL @ 66 psi (0.45 MPa) (OC) - (78-102)</p> |
| <b>Cartridge Specification</b>                          | <p>Fittings : Components have WRAS Approved for food grade conformity with Brass Housing and Spindle</p> <p>Life Cycle EN 200: 200,000 cycles (Standard)</p> <p>- 4.0 LAC Cycles as per EN 200*</p>   |
| <b>Water Tightness</b>                                  | 12 bar (Pass)   |
| <b>Pressure Resistance</b>                              | 20 bar (Pass)   |
| <b>Finish</b>   | <p>Plating: Nickel-8.0 micron Chromium-0.20 micron</p> <p>Salt Spray (300 hrs + Validated)</p> <p>Adhesion (Pass)</p>   |
| <b>Available Colour Finishing</b>                       | Chrome (CHR)  |

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.