

esscobathware.com Document No. SNW/AIS/24/853S300SPPSM








TOP VIEW





enera	Information	

General Information	
Product Code	AIS-WHT-101853S300SPPSM
Brand	Essco
Colour	White
Туре	Single Piece WC (S-Trap)
Material	Ceramic-Vitreous China (VC)
Product Specification	
Product Dimension	360x680x730 mm
Bowl Opening (Inner Dimension)	250x330 mm
Product Net Weight	49 kg
Product Gross Weight	55 kg
Packaging Dimension	680x360x730
Outlet	Vertical
Trap Distance	S Trap - 300 mm

	W
	Ar
Droduct Foatures	

Sleek And Stylish Design With Rectangular Shape PP Slim Soft Close Seat Cover ater Usage - 3/6 LPF With Wash Down Flushing

External diameter of outlet hole dia. Ø 100 ± 5 mm

nti Bacterial Glaze on Ceramic Smooth Glaze Surface Material - Vitreous China (VC)

Product With Complete Genuine Accessories

Complete Trap Wash

ACCESSORIES INCLUDED

Outlet Hole Dimension

Seat Cover	AIS-WHT-103S
Floor fixing screw	ZPS-SNS-FB01
Cistern Fittings	ZCF-WHT-FT002
Wax Seal	ZPS-WHT-1401

CARE AND CLEANING GUIDELINES

¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter

Horizontal distance between the wall line and the centre line of the waste outlet hole ≤ 300 mm

- The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ¬ Carefully inspect the new product for damage before installation.
- ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- \neg Risk of external leakage. Do not lift or rock the bowl after placement.
- ¬ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- Do not allow cleaners to sit or soak on the product.
- use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¹ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001





DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. All dimensions are in mm (Tolerance \pm 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product