			4	
esscobathware.com			ESSCO	
Document No.				
SNW/CMS/24/751P180SPP				
		-175-	400	
225				
665]		69	
345	,		4	
	275 365		° I ST	
L /L			9	
	<u> </u>	5	$\uparrow \square \square$	
			F.F.Lvl.	
		180	P-TRAP 180- Ø100	
TOP VIEW		SIDE VIEW	BACK VIEW	
General Information	CNAS 14/11T 4007540400			
Product Code		DSPP + CMS-WHT-103201		
Brand	Essco			
Colour	White			
Туре	Coupled WC (P-Trap)			
Material	Ceramic-Vitreous China	a (VC)		
Product Specification	·			
Product Dimension	400x665x810 mm			
Bowl Opening (Inner Dimension)	275x345 mm			
Product Net Weight	32.3 Kg			
Product Gross Weight	43.2 Kg			
Packaging Dimension	680x450x435 mm			
Outlet	Horizontal			
Trap Distance	P Trap - 180 mm			
External diameter of outlet hole dia.				
Outlet Hole Dimension				
	• • •	Beautiful Design ,Complete Trap Glaze, Combined Packing PP Soft Close Slim Seat Cover with Accessories		
Product Feature	Dual Flushing - 3/6 LPF, Anti germ glaze.			
	Material - Vitreous China (VC)			
ACCESSORIES PROVIDED				
Seat Cover	CMS-WHT-101S			
Floor fixing screw	ZPS-SNS-FB01			
Cistern	CMS-WHT-103201C			
Cistern Fittings	ZCF-WHT-FT003			
CARE AND CLEANING GUIDELINES	la la matrix de la del		all along the state of the stat	
 Vitreous china sanitary ware products are frag use thereafter. 	ie in nature and need to b	be nandled with care (to avoid personal injury) at	all times during its storage, handling, installation and	
\neg The product is heavy and it is recommended the theorem of the product is heavy and it is recommended the theorem of the product is heavy and it is recommended the product is recommended the product is recommended the product is recomme	iat two persons hold it wh	nie it is being fixed.		
\neg Carefully inspect the new product for damage	before installation.			
\neg Risk of product damage. Over tightening may $lpha$	ause breakage or chipping	g of vitreous china.		
¬ Risk of external leakage. Do not lift or rock the	bowl after placement.			
	-	lust hoforo applying it to the active surface		
 Always test your cleaning solution on an incon 	spicuous area on the prod	nuct before applying it to the entire surface.		
\neg Do not allow cleaners to sit or soak on the pro-	duct.			
\neg Use a soft, dampened sponge or cloth to clean	. Never use abrasive mate	erial like a bristle brush or scouring pad.		
 Wipe surfaces clean and rinse completely with 	water immediately after	applying cleaners.		
- Clean Chrome, stainless steel surfaces once a v		containing chloride on chrome, stainless steel. If	used, rinse the surface immediately to prevent	
corrosion.	etc. uco only units and	to clean and than drawith a soft state		
	cts, use only warm water	to clean and then dry with a soft cloth.		
	TCM	CE		
QUALITY MANAGEMENT SYSTEM - ISO 9001	SUD INC OWN			
DISCLAIMER: Our every effort has been made to ensu dimensions are in mm (Tolerance ± 5 MM). Jaquar re # For Installation Refer Actual Product			ments in different sites, markets and/ or countries. All tice.	