





DescriptionBasin Tap 1/2 InchFlow Rate14.23 LPM @ 3 barBy using flow regulators (Product should be ordered with suffix as G-2.5 LFlow regulator6.0 LPM, GB-8.0 LPM, & GD-3.8 LPM, GE-1.3 LPM @ 4.0 Bar pressure) on	
By using flow regulators (Product should be ordered with suffix as G-2.5 L	
1, 5, 5, 5, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7,	
regulate the flow rate.	-
Recommended Water Pressure 0.5 Bar - 5 Bar	
Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0 Total Impurity (0.0-2.0), Zn (Remainder))-0.5),
Cartridge Specification Fittings: Components have WRAS Approved for food grade conformity w Housing and Spindle Life Cycle EN 200: 200,000 cycles (Standard) - 4.0 LAC Cycles as per EN 200*	ith Brass
Water Tightness 12 bar (Pass)	
Pressure Resistance 20 bar (Pass)	
Plating: Nickel-8.0 micron Chromium-0.20 micron Salt Spray (300 hrs + Validated) Adhesion (Pass)	
Aerator Size M22X1 mm	
Available Colour Finishing Chrome (CHR)	

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.