





| Product Code | MQT-CHR-517KN |
|--|--|
| Description | Bath & Shower Mixer with Telephone Shower Crutch, Wall Mounted |
| Flow Rate | 25.60 LPM @ 3 bar |
| Flow regulator | By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 LPM, GB-8.0 LPM, & GD-3.8 LPM, GE-1.3 LPM @ 4.0 Bar pressure) one can regulate the flow rate. |
| Recommended Water Pressure | 0.5 Bar - 5 Bar |
| Material Composition Specification in Percentage | Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder) Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) S.S Sheets as per AISI : 304 Ni (8.0-11.0), Ch (18.0-20.0), Mn (0.0-0.2), Ca (0.0-0.08), Ir (Remainder) ABS - Specific Gravity (g/cm2) - (1.06-1.10), Melt Mass Flow Rate (g/10 min.) - (20-26), Rockwell Hardness - (95-115), DTUL @ 66 psi (0.45 MPa) (0C) - (78-102 |
| Cartridge Specification | Fittings: Components have WRAS Approved for food grade conformity with Brass Housing and Spindle Life Cycle EN 200: 200,000 cycles (Standard) - 4.0 LAC Cycles as per EN 200* |
| Water Tightness | 12 bar (Pass) |
| Pressure Resistance | 20 bar (Pass) |
| Finish | Plating: Nickel-8.0 micron Chromium-0.20 micron Salt Spray (300 hrs + Validated) Adhesion (Pass) |
| Aerator Size | M28X1mm |
| Available Colour Finishing | Chrome (CHR) |
| DISCLAIMER: Our every effort ha | s heen made to ensure factual accuracy, the information presented subject to |

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.