



| | |
|--|--|
| Product Code | ORI-CHR-109011B |
| Description | Single Lever Basin Mixer without Popup Waste, with 375mm Long Braided Hoses |
| Connection Size | Braided hoses, 1/2" FIP (ACS Approved) Withstand pressure of 10 Bar |
| Flow Rate | 11.55 LPM @ 3 bar |
| Flow regulator | By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 LPM, GB-8.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 4.0 Bar pressure) one can regulate the flow rate. |
| Recommended Water Pressure | 0.5 Bar - 5 Bar |
| Material Composition Specification in Percentage | <p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> |
| Cartridge Specification | <p>NSF-61 Approved Cartridge with Temperature Limiter</p> <p>Cartridge with Brass Spindle</p> <p>Life Cycle EN 817: 70,000 cycles (Standard)</p> <p>- 1.40 LAC Cycles as per EN 817*</p> <p>- 7.0 LAC Cycles (ON/OFF)*</p> |
| Water Tightness | 12 bar (Pass) |
| Pressure Resistance | 20 bar (Pass) |
| Finish | <p>Plating: Nickel-8.0 micron Chromium-0.20 micron</p> <p>Salt Spray (300 hrs + Validated)</p> <p>Adhesion (Pass)</p> |
| Aerator Size | M22X1mm |
| Available Colour Finishing | Chrome (CHR) |
| <p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaguar reserves the right to make the necessary amendments at any time without prior notice.</p> | |